:Fabbian

Pivot

F39G04A76

Vittorio Massimo



Fixture Type Project Name





Dimensions



Description

Lampada da parete/soffitto con struttura in alluminio anodizzato bronzo. Corpo illuminante orientabile.

Voltage

24Vdc

Specs



DRY



Material

Aluminium

Color



Light source

LED 1x46W-120° 2700K 5000lm Cri >90

Other colors available

Check online www.fabbian.us

Notes

Available 120- 277Vac; Available 0-10V dimming System compatible with the following Lutron 24V Drivers 96W HiLume Premier L3D0 24V Const Voltage PWM 0.1% and SoftOn/FadeToBlack 49W Hi-Lume 1% Dimming (2-wire Forward Phase) LTE

Included accessories

LED

Not included accessories

System requires a remote driver. Choose from ELV, 0-10V, or compatible Lutron drivers. Reference fabbian.us for current options.


Weight Lamp

Net: 0 lb

Packaging

Gross weight: 3.48 lb Volume: 0.5600000000000001 ft3 Number of boxes:

In the same family



Pivot F39

Other options

	code	electrification	technical info	
	F39 G01 A 01	LED 24Vdc x23W-120° 3000K 2500 Cri >90	DRY CONTROL DRY CONTROL	White
47/8° 47/8° 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1	F39 G02 A 01	LED 24Vdc x23W-120° 2700K 2500lm Cri >90	DRY Cocy	White
	F39 G01 A 21	LED 24Vdc x23W-120° 3000K 2500 Cri >90	DRY Constitution of the Co	Anthracite
	F39 G02 A 21	LED 24Vdc ×23W-120° 2700K 2500lm Cri >90	DRY Comments	Anthracite
	F39 G01 A 76	LED 24Vdc x23W-120° 3000K 2500 Cri >90	DRY Comments of the control of the c	Bronze
	F39 G02A 76	LED 24Vdc x23W-120° 2700K 2500 Cri >90	DRY Constant DRY Constant	Bronze

	F39 G03 A01	LED 24Vdc x46W -120° 3000K 5000lm CRI>90	BRY CONTROL DRY ANALYSIS	White
4 7/00" 4 7/00" 1 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	F39 G04 A01	LED 24Vdc x46W -120° 2700K 5000lm CRI>90	DRY CONTROL DRY AUGUST	White
	F39 G03 A21	LED 24Vdc x46W -120° 3000K 5000Im CRI>90	DRY CSO MERCENS	Anthracite
	F39 G04 A 21	LED 24Vdc x46W-120° 2700K 5000Im Cri >90	DRY CONTROL	Anthracite
	F39 G03 A 76	LED 24Vdc ×46W-120° 3000K 5000 Cri >90	DRY Control DRY Registration	Bronze
	F39 G04 A 76	LED 24Vdc ×46W-120° 2700K 5000 Cri >90	BRY Corporate DRY Automatic	Bronze

	F39 G05 A01	LED 24Vdc x70W-120° 3000K 7500 Cri >90	DRY Cappoint Statement Control of Statement Control	White
47/8° 47/8° 25 27/8° 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	F39 G06 A01	LED 24Vdc ×70W-120° 2700K 7500 Cri >90	DRY Copy Account.	White
	F39 G05 A21	LED 24Vdc x70W-120° 3000K 7500 Cri >90	DRY Capper Control of the Control of	Anthracite
	F39 G06 A 21	LED 24Vdc x70W-120° 2700K 7500lm Cri >90	DRY Copy description	Anthracite
	F39 G05 A 76	LED 24Vdc ×70W-120° 3000K 7500 Cri >90	DRY Companies	Bronze
	F39 G06 A 76	LED 24Vdc ×70W-120° 2700K 7500 Cri >90	DRY Control	Bronze