# :Fabbian

Freeline
F44L03A02
Flynn Talbot

Fixture Type

Project Name

Description
A black aluminium spot light with a lens with electrification on mains voltage for LEDs.

Voltage	Dimmable	Specs
24Vdc	0-10V	ETL Intertek DRY 360° ADJUSTABLE SYSTEM

Light source
LED 1x8W-10°
2700K
934lm Cri >90

Notes
Cable 157"
System compatible with the following Lutron 24V Drivers
96W HiLume Premier L3D0 24V Const Voltage PWM 0.1% and SoftOn/FadeToBlack
49W Hi-Lume 1% Dimming (2-wire Forward Phase) LTE

Included accessories
LED

Not included accessories
Component Only as part of system; Drivers, System Connectors Not Included. Reference www.fabbian.us for drivers, connectors, and other system options

Weight Lamp
Net: 1.17 lb

Packaging
Gross weight: 1.41 lb
Volume: 0.18 ft³
Number of boxes: 1

Dimensions

5 1/16"

Ø2 5/16"

Material
Aluminium

Color
■ Black

Freeline F44

Other options

	code		electrification	technical info
	F44 L01	02	LED 24Vdc 1x8W-10° 3000K 934lm Cri >90	ETL Intertek DRY 360° ADJUSTABLE SYSTEM
	F44 L03	02	LED 24Vdc 1x8W-10° 2700K 934lm Cri >90	ETL Intertek DRY 360° ADJUSTABLE SYSTEM
	F44 L02	02	LED 24Vdc 1x8W-10° 3000K 934lm Cri >90	ETL Intertek DRY 360° ADJUSTABLE SYSTEM
	F44 L11	02	LED 24Vdc 1x8W-120° 3000K 934lm Cri >90	ETL Intertek DRY 360° ADJUSTABLE SYSTEM
	F44 L13	02	LED 24Vdc 1x8W-120° 2700K 934lm Cri >90	ETL Intertek DRY 360° ADJUSTABLE SYSTEM
	F44 L04	02	LED 24Vdc 1x8W-10° 2700K 934lm Cri >90	ETL Intertek DRY 360° ADJUSTABLE SYSTEM
	F44 L12	02	LED 24Vdc 1x8W-120° 3000K 934lm Cri >90	ETL Intertek DRY 360° ADJUSTABLE SYSTEM
	F44 L21	02	LED 24Vdc 1x8W-120° 3000K 934lm Cri >90	ETL Intertek DRY 360° ADJUSTABLE SYSTEM
	F44 L23	02	LED 24Vdc 1x8W-120° 2700K 934lm Cri >90	ETL Intertek DRY 360° ADJUSTABLE SYSTEM
	F44 L14	02	LED 24Vdc 1x8W-120° 2700K 934lm Cri >90	ETL Intertek DRY 360° ADJUSTABLE SYSTEM

F44 L22	02	LED 24Vdc 1x8W-120° 3000K 934lm Cri >90		ETL Intertek DRY 360° ADJUSTABLE SYSTEM
F44 L24	02	LED 24Vdc 1x8W-120° 2700K 934lm Cri >90		ETL Intertek DRY 360° ADJUSTABLE SYSTEM