

Freeline F44L12A02

Flynn Talbot



Fixture Type
Project Name



Description

Voltage
24Vdc

Dimmable
0-10V

Specs



DRY



Material
Aluminum

Light source

LED 1x8W-120°
3000K
934lm Cri 90

Color

■ Black

Notes

Cable 393"
System compatible with the following Lutron 24V Drivers
96W HiLume Premier L3D0 24V Const Voltage PWM 0.1% and SoftOn/FadeToBlack
49W Hi-Lume 1% Dimming (2-wire Forward Phase) LTE

Other colors available

Check online www.fabbian.us


Included accessories

LED

Not included accessories





















Component Only as part of system; Drivers,
System Connectors Not Included.
Reference www.fabbian.us for drivers,
connectors, and other system options

Dimensions



Freeline F44

Other options

	code		electrification	technical info
	F44 L01	02	LED 24Vdc x8W-10°/30° 3000K 934lm Cri 90	  
	F44 L02	02	LED 24Vdc x8W-10°/30° 3000K 934lm Cri 90	  
				
	F44 L11	02	LED 24Vdc x8W-120° 3000K 934lm Cri 90	  
	F44 L12	02	LED 24Vdc x8W-120° 3000K 934lm Cri 90	  
				
	F44 L21	02	LED 24Vdc x8W-120° 3000K 934lm Cri 90	  
	F44 L22	02	LED 24Vdc x8W-120° 3000K 934lm Cri 90	