
## : Fabbian

## Olympic F45A11A01

### Lorenzo Truant



Fixture Type Project Name





#### Description

Composition with the three pendants with white painted aluminium structure and plastic material diffuser.

Dimmable Voltage 120V/24V 0-10V



Light source


LED 1x230W-120° 3000K (2700K delivered) 24850lm (12425 delivered lumens) Cri >90 0-10V Dimming

#### Notes

Composition with the three suspensions 277V Available

#### **Included accessories**

LED 0-10V Dimmable electronic driver Dimensions



Material Aluminum - Plastic

Color

White

Other colors available Check online www.fabbian.us

#### In the same family



Pendant

# Olympic F45 Other options

	code	electrification	technical info
	F45 A01 A 01 F45 A01 A 76	LED 120V/24V x56W-120° 3000K (2700K delivered) 6000Im (3000 delivered lumens) Cri 0-10V Dimming	@ DRY >90
To serve, To serve,	F45 A02 A 01 F45 A02 A 76	LED 120V/24V 1x56W-120° 2700K (2400K delivered) 6000Im (3000 delivered lumens) Cri >90 0-10V Dimming	DRY

	F45 A03 A 01 F45 A03 A 76	LED 120V/24V x76W-120° 3000K (2700K delivered) 8250Im (4125 delivered lumens) Cri >90 0-10V Dimming
	F45 A04 A 01 F45 A04 A 76	LED 120V/24V 1x76W-120° 2700K (2400K delivered) 8250lm (4125 delivered lumens) Cri >90 0-10V Dimming

	F45 A05 A 01 F45 A05 A 76	LED 120V/24V x98W-120° 3000K (2700K delivered) 10600Im (5300 delivered lumens) Cri 0-10V Dimming	
difference in the second secon	F45 A06 A 01 F45 A06 A 76	LED 120V/24V 1x98W-120° 2700K (2400K delivered) 10600Im (5300 delivered lumens) Cri 0-10V Dimming	i >90

Fabbian Usa Corp. | 307 W 38th St Ste 1103, New York, NY 10018 (USA) | ph. +1 646 518 4160 | fax +1 646 518 4180 | www.fabbian.us | usa@fabbian.com canada@fabbian.com

Pictures, descriptions, dimensions and technical data have to be considered as purely indicative. While maintaining the basic characteristics of the product, the manufacturer reserves the right to make modifications at any time with the sole aim of improvement.

And the second s	F45 A05 A 01 F45 A05 A 76	LED 120V/24V x98W-120° 3000K (2700K delivered) 10600Im (5300 delivered lur 0-10V Dimming	DRY nens) Cri >90	
	F45 A06 A 01 F45 A06 A 76	LED 120V/24V 1x98W-120° 2700K (2400K delivered) 10600Im (5300 delivered lur 0-10V Dimming	₩. DRY nens) Cri >90	

	F45 A11 A F45 A11 A	01 76	LED 120V/24V x230W-120° 3000K (2700K delivered) 24850Im (12425 delivered lumens) Cri 0-10V Dimming	
De traine De traine D	F45 A12 A F45 A12 A	01 76	LED 120V/24V 1x230W-120° 2700K (2400K delivered) 24850Im (12425 delivered lumens) Cri 0-10V Dimming	. <b>DRY</b> >90

Pictures, descriptions, dimensions and technical data have to be considered as purely indicative. While maintaining the basic characteristics of the product, the manufacturer reserves the right to make modifications at any time with the sole aim of improvement.