


Light Glide F57A51A02

Cory Grosser




Fixture Type

Project Name



Dimensions



Description

Linear linear pendant that provides direct and indirect illumination. Black anodized finish. 0-10V dimming with independent operation of direct and indirect sources.

Voltage

120V-277V (UNV)

Dimmable

0-10V

Specs



DRY IP40

Material

Aluminum, prismatic PMMA

Light source and Technical

Lamp Type: LED

Wattage: 50 Watt

Color Temperature: 3000K

CRI: 90+

Lumens: Source - Up: 2083 lm Down: 4168lm; Delivered - Up: 1417 lm Down: 2959 lm

Average LED Life: 50,000 hours L80/B10

Operating Temperature: 14~113°F (-10~45°C)

Notes

Low Glare

Flicker-Free

3 McAdam Step binning

Included accessories

LED

Not included accessories

Color

■ Black

Other colors available

Check online www.fabbian.us

Weight Lamp


Net: 17lb(7.7Kg)

Light Glide F57

Other options




code	electrification	technical info	color
F57 A11 A 02 F57 A11 A 01	150W 120-277(UNV) 3000K LED	DRY	Black White



F57 A13 A 02 F57 A13 A 01	150W 120-277(UNV) 4000K LED	DRY	Black White
--	-----------------------------	-----	----------------



F57 A51 A 02 F57 A51 A 01	50W120-277(UNV) 3000K LED	DRY	Black White
--	---------------------------	-----	----------------



F57 A53 A 02 F57 A53 A 01	50W120-277(UNV) 4000K LED	DRY	Black White
--	---------------------------	-----	----------------